

Hourmeters



TM Series


- 2 in. (51 mm) Diameter Dial
- Tamperproof and Environmentally Sealed
- Mechanical Counter–No Battery Needed to Maintain Elapsed Time
- Reversed Polarity Protected
- Quartz-Crystal Time Base for Accurate Long-Term Timekeeping
- Powered by 12 to 24 VDC

Description

The TM Series hourmeters record the operating time of vehicles or powered equipment. They are electromechanical and have a quartz base time counter that insures accuracy (better than $\pm 0.02\%$ over the entire range). They can record up to 99,999.9 hours (9,999.9 for TM612/624) and include an automatic recycle to zero hours feature. The TM Series models have a shock-proof and tamperproof, totally sealed case made of an engineered plastic. These small, light weight time meters are rugged and durable. They are the answer to applications requiring a low DC power, reliable hourmeter.

The TM612/624 model includes a 3-hole mounting shock ring for extreme-shock protection.

Bezels



Basic Models

6-Digits Hourmeters	
Model	Bezel Type
TM4592	Bright Stainless Steel Bezel
TM4593	Black Stainless Steel Bezel
TM4594	SAE Bright Stainless Steel Bezel
TM4595	SAE Stainless Steel Black Bezel

5-Digits Hourmeter with Shock Ring Mounting TM612/624 3-Hole Mount, Black Bezel

Applications

These hourmeters can be used on any engine where operating time needs to be recorded. All it requires is a DC power source (refer to Specifications, at right).

Outstanding Features

- Solid-State Electronic Drive Circuit
- Quartz-Crystal for Accurate Timing
- Quiet Operation-Permanently Lubricated
- High-Impact, Tamperproof Plastic Case
- Sealed Against Moisture and Dirt
- Indicates Operating Time in Hours and Tenths
- No Battery Back Up Required
- Made in the U.S.A.

Specifications

Power Input: 12 to 24 VDC Power Consumption: Less than 0.03 W @ 12 VDC; 0.4 W @ 24 VDC. Accuracy: $\pm 0.02\%$ over entire range. **Temperature Range:** -40° F to 185° F (-40° C to $+85^{\circ}$ C). Dial (Face Plate): White numerals (over black background). Time Scale: TM4592-95 models: 6-digits 99,999.9 hours; TM612/624 models: 5-digits 9,999.9 hours. Automatic recycle to zero. Vibration Resistance: Withstands 10 to 75 Hz @ 1 to 8 G's. Case Material: Plastic. Bezel: Stainless Steel. Terminations: 1/4 in. (6 mm) male blade terminals. TM4592/4595 Shipping Weight: 5 ozs. (140 g). Shipping Dimensions: 3-1/8 x 3 x 3 in. (79 x 76 x 76 mm) approximately. TM612/624 Shipping Weight: 8 ozs. (230 g). TM612/624 Shipping Shipping Dimensions: 5 x 5 x 3-1/4 in. (127 x 127 x 83 mm) approx. Warranty

A two-year limited warranty on materials and workmanship is given with this Murphy product. Details are available on request and are packed with each unit.

* Products covered by this bulletin comply with EMC Council directive 89/336/EEC regarding electromagnetic compatibility except as noted. The CE mark does not apply to the TM612 and TM624 models.

