


NEF 250

N40 ENT M25

FOR MARINE APPLICATIONS
4 CYLINDERS IN LINE - DIESEL CYCLE
184 kW (250 CV) @ 2800 rpm (A1)
147 kW (200 CV) @ 2800 rpm (B)
125 kW (170 CV) @ 2800 rpm (C)



T E C H N O L O G I C A L E X C E L L E N C E

IVECO
MOTORS

N40 ENT M25 FOR MARINE APPLICATIONS

Thermodynamic cycle		Diesel 4 stroke - C.R.
Air intake		TAA
Arrangement		4L
Bore x Stroke	mm	102 X 120
Total displacement	l	3.9
Valves per cylinder		4
Cooling		liquid
Direction of rotation (viewed facing flywheel)		CCW
Compression ratio		16 to 1
Rotation mass moment of inertia (without flywheel)	kgm ²	0.16
Standard flywheel inertia	kgm ²	0.7

Air induction

Max suggested intake restriction with clean air filter	kPa(bar)	3.5 (0.035)
Max allowable restriction with dirty air filter	kPa(bar)	6.5 (0.065)
Air requirement for combustion at 100% load/rated speed (comb. + ventilation)	kg/h (m ³ /h)	4600 (4000)
Turbocharging pressure at full load/rated speed	kPa(bar)	190 (1.9)
Turbocharging air max temperature (engine inlet)	°C	50

Exhaust system

Max allowable backpressure	kPa(bar)	7 (0.070)
Max exhaust temperature at maximum power	°C	650
Exhaust flow at max output	kg/h	1080

Lubrication system

Minimum oil pressure at idle (at 100°C)	kPa(bar)	70 (0.7)
Max oil temperature at full load/rated speed	°C	120
Engine angularity limits continuous operation: max front up and front down	0/360	20°
max left hand and right hand	0/360	30°
Total system capacity including pipes, filters etc.	liters	12.5

Sea water cooling system (open circuit)

Max intake restriction	kPa(bar)	20 (0.2)
Sea water pump flow	m ³ /h	12
Heat rejected (total) at max power	kJ/s(kcal/h)	149 (128,000)
Sacrificial zinc anodes	n°	2

Cooling system (closed circuit)

Coolant capacity (engine only)	liters	21.5
Water pump flow at rated speed	m ³ /h	15
Thermostat (modulating range)	°C	78 to 87
Cooling liquid max temperature	°C	106
Min/max inner pressure in the cooling circuit (for keel cooling)	kPa(bar)	10/100 (0.1/1)
External cooling system max pressure drop (for keel cooling)	kPa(bar)	35 (0.35)

Fuel system

Injection system		Common Rail
Gas oil max intake restriction	kPa(bar)	35 (0.35)
Gas oil max intake temperature	°C	70
Max fuel backpressure to tank	kPa(bar)	20 (0.2)

Electrical system


Voltage	V	12
---------	---	----

N40 ENT M25 FOR MARINE APPLICATIONS

Rating type		A1	B	C
Maximum power *	kW(CV)	184 (250)	147 (200)	125 (170)
At speed	rpm	2800	2800	2800
Maximum no load governed speed at max rating	rpm	3000	3000	3000
Minimum idling speed	rpm	700	700	700
Mean piston speed at rated speed	m/s	11,2	11,2	11,2
BMEP at max torque	kg/cm ²	22.1	18.3	15.6
Specific fuel consumption at full load (best value)	g/kWh @ rpm	212 @ 2400		
Oil consumption at max rating	(% of fuel consumption)	0.1		
Minimum starting temperature without auxiliaries	°C	-10		
Oil and oil filter maintenance interval for replacement	hours	600		
Dry weight (without marine gear)	kg	490		

* **Net Power** at flywheel according to ISO 3046/1, after 50 hours running, fuel Diesel EN 590. Power tolerance 5%

Test conditions : ISO 3046/1, 25 °C air temperature, 100 kPa atmospheric pressure, 30 % relative humidity.



A1 = High performance crafts.
Full throttle operation restricted within 10% of total use period.
Cruising speed at engine rpm < 90% of rated speed setting - Maximum useage 300 hours per year.


B = Light duty.
Full throttle operation restricted within 10% of total use period.
Cruising speed at engine rpm < 90% of rated speed setting - Maximum useage 1500 hours per year.

C = Medium duty.
Full throttle operation < 25% of use period.
Cruising speed at engine rpm < 90% of rated speed setting - Maximum useage 3000 hours per year.

L = 983 mm

W = 780 mm

H = 785 mm



N40 ENT M25 FOR MARINE APPLICATIONS

Standard configuration

Flywheel housing	SAE	3
Flywheel size	inch	11 ½
Air filter		rear side
Turbocharger		water cooled
Heat exchanger		tube type
Exhaust cooled elbow		-
Water charge tank		included
Fuel filter	n°	1
Fuel prefilter		included (loose)
Fuel pump		included
Oil filter	n°	1
Oil sump		aluminium
Oil vapours blow-by circuit		rear
Oil heat exchanger		built in the crankcase
Oil filler		on timing cover
Starting motor		12 V - 3 kW
Alternator		12 V - 90 A
Engine stop device		by electronic central unit
Wiring harness		with EDC (Electronic Diesel Control)
Painting	colour	white "ICE"

Not included in the standard configuration

Battery - minimum capacity recommended	120 Ah
Battery - minimum cold cranking capacity recommended	900 A

IVECO MOTORS OFFERS THE WIDEST AVAILABILITY OF ENGINE BUILD OPTIONS TO CUSTOMER SPECIFIC REQUIREMENTS WITHIN THE ENGINE SUPPLY. TO FIND OUT MORE ABOUT THE CONFIGURATIONS AND ACCESSORIES WHICH ARE AVAILABLE, CONTACT THE IVECO MOTORS SALES NETWORK.

HEAD OFFICE AND BRANCHES

IVECO S.p.A. Iveco Motors Via Puglia, 15 - 10156 Torino Tel. +39 (011) 0076245 - Fax +39 (011) 0076275 www.ivecomotors.com	Italy	IVECO S.p.A. Iveco Motors Viale dell'Industria, 15/17 - 20010 Pregnana Milanese - Milano Tel. +39 (02) 935101 - Fax +39 (02) 93590029	Italy
IVECO FRANCE S.A. Iveco Motors 50 Rue Ampère - B.P. 103 - 69685 Chassieu Cedex Tel. +33 (04) 72472222 - Fax +33 (04) 78905990	France	IVECO S.p.A. Branch Office India Second Floor - 50, Okhla Industrial Estate - Phase III 110020 New Delhi Tel. +91 11 51001417 - Fax +91 11 26931271	India
IVECO MAGIRUS A.G. Iveco Motors Heiner Fleischmann-Strasse, 9 - 74172 Neckarsulm Tel. +49 (07132) 97690 - Fax +49 (07132) 976935	Germany	IVECO FIAT 10/F Jinling Hotel World Trade Center 2 Hanzhong Road - 210005 Nanjing Tel. +86 25 84710981 - Fax +86 25 84701105	China
IVECO U.K. Ltd Iveco Motors Road One - Industrial Estate CW7 3QP Winsford Tel. +44 (01606) 541027 - Fax +44 (01606) 541124	Great Britain	IVECO LATIN AMERICA Ltda. Iveco Motors Rua Alameda da Serra, 222 Vale do Sereno - 34000 - 000 Nova Lima (MG) Tel. +55 31 3286 3732/33/34 - Fax +55 31 3286 3735	Brazil
IVECO SWEDEN A.B. Iveco Motors Transportgatan, 59 - 42246 Hisings Backa Tel. +46 (31) 492450 - Fax +46 (31) 492457	Sweden	IVECO Motors of N.A. 245 E. North Avenue Carol Stream, IL 60188 - 2021 USA Tel. +1 630 260 4226 - Fax +1 630 260 4267	North America

Local Distributor